Model 239-1F with 2350-1 Floor Contamination Monitor



Features

- Adjustable Detector Height
- Digital Ratemeter/Scaler/Logger
- Auto-Ranging, 5-Decade Range
- 425 cm² Gas Proportional Detector
- Rugged Roll-around Cart

Introduction

This system features a flow system, quick-connects, gas bottle mount, and height-adjustable detector for optimum floor-monitoring performance. A nuclear counting gas bottle and gas regulator are required for the operation of the floor monitor. This system is supplied with the 5-decade, auto-ranging Model 2350-1 General Purpose Ratemeter/Scaler/ Data Logger that features a large backlit LCD display.

Specifications

Part Number: 48-2594

INDICATED USE: floor monitoring for alpha, beta-gamma

DETECTOR: gas proportional

RECOMMENDED COUNTING GAS: P-10 (10% methane; 90% argon)

CYLINDER SIZE: will hold a cylinder 15.2 cm x 48.3 cm (6 x 19 in.) (Dia x H) or smaller (Linde size "Q", Matheson size 3, Airgas size "R")

WINDOW: 0.8 mg/cm² aluminized Mylar (window thicknesses of 0.4, 3.9,

or 7.9 mg/cm² are available)

ACTIVE AREA: 584 cm²

OPEN AREA: 425 cm²

EFFICIENCY (4 π): 17%–²³⁹Pu; 25%–⁹⁰Sr/⁹⁰Y; gamma < 1% **GAS RECHARGE:** will operate on static charge for 2 hours

DETECTOR HEIGHT: adjustable from 0.32–7.6 cm (0.125–3 in.) from surface

DETECTOR OPERATING VOLTAGE:

ALPHA: typically 1000–1200 volts BETA GAMMA: typically 1600–1800 volts

THRESHOLD: typically 2–4 mV

FLOW METER:

IN: adjustable from 0–100 cc/min **OUT:** flow indicator from 0–100 cc/min

CONCLUMPTION true inclus 50 as (as in

GAS CONSUMPTION: typically 50 cc/min

GAS CONNECTORS: double-end quick disconnect for 0.6 cm (0.25 in.) OD tubing **CONSTRUCTION:**

DETECTOR: anodized aluminum housing with stainless steel hex protective screen (79% open) **CART:** 2.5 cm (1 in.) square tubular steel and aluminum with beige powder coat paint, 19.1 cm (7.5 in.) diameter rear wheels, and 10.2 cm (4 in.) diameter swivel casters

Model 2350-1 face, shown with

handle removed for clarity

DETECTOR SIZE: $2 \times 16 \times 46.5 \text{ cm} (0.8 \times 6.3 \times 18.3 \text{ in.}) (H \times W \times L)$

CART ASSEMBLY: 106.7 x 40.6 x 69.9 cm (42 x 16 x 27.5 in.) (H x W x L) (excluding detector) **WEIGHT:** 11.4 kg (25 lb), excluding gas bottle and counting instrument



(gas bottle not included)

Ludium Measurements, Inc. P.O. Box 810, Sweetwater, Texas 79556 Web: http://www.ludiums.com Tel: 800-622-0828 / 325-235-5494 / Fax: 325-235-4672 / Email: sales@ludiums.com Note: specifications subject to change without notification. We are not responsible for errors or omissions.