

# Model 375-30 Landfill / Transfer Station Monitor

*Radiation Detection for a Safer World*



Ludlum Measurements, Inc.

## Features

- Affordable Digital Controller
- 2 Weatherproof Encased Shielded Sodium Iodide [NaI (TI)] Detectors
- User-Adjustable Alarms
- Networkable
- 48-Hour Battery Backup
- Includes 61 m (200 ft) Cables
- 10  $\mu\text{Ci}$   $^{137}\text{Cs}$  Check Source Included



Part Number: 48-2601

## Introduction

This simple and cost-effective landfill / transfer station monitor consists of two weatherproof, lead-shielded detectors coupled to the Ludlum Model 375 Controller. The adaptable, compact, networkable controller's digital design make setup, customization, and operation of the system easy.

The controller is typically mounted indoors near the operator to take advantage of its ability to supply local alarms, but it may also be connected to external alarms or networked into the Ethernet, (with optional accessories). A 48-hour battery backup ensures operation in event of loss of external power.

## Specifications

**DETECTORS:** 2 ea. 7.6 x 2.5 cm (3 x 1 in.) shielded sodium iodide [NaI(Tl)] scintillation detectors in NEMA 4x weathertight enclosures

**DISPLAY:** 4-digit LED display with 2 cm (0.8 in.) characters

**DISPLAY UNITS:** kcpm

**STATUS:** (green light) instrument functioning properly

**LOW ALARM:** (yellow LOW ALARM light and slow beep) can be set at any point from 0.0 to 9999

**HIGH ALARM:** (red HIGH ALARM light and fast beep) can be set at any point from 0.0 to 9999

**LOW BAT:** (yellow light) indicates less than 2 hours of battery power remaining

**OVERLOAD:** senses detector saturation (indicated by display reading "-OL-")

**OVERRANGE:** the radiation field being measured has exceeded counting range of instrument (indicated by display reading "- - -")

**AUDIO OUTPUT:** intensity is user-adjustable, DET FAIL indicated by audible tone greater than 68 dB at 0.6 m (2ft)

**REMOTE (optional):** allows for connection of red strobe for remote indication of an alarm

**POWER:** 95 to 135 Vac (178 to 240 Vac available), 50 to 60 Hz, 6-volt sealed lead-acid rechargeable battery (built-in)

**BATTERY LIFE:** typically 48 hours in non-alarm condition, 12 hours in alarm condition

**BATTERY CHARGER:** battery is continuously trickle-charged when instrument is connected to line power and turned on

**CONSTRUCTION:** aluminum housing with ivory powder coat

**TEMPERATURE RANGE:** -20 to 50 °C (-4 to 122 °F)

**SIZE:** electronics: 18.7 x 24.6 x 6.4 cm (7.4 x 9.7 x 2.5 in.) (H x W x L)

detectors: 33 x 43.2 x 21.6 cm (13 x 17 x 8.5 in.) (H x W x L)

**WEIGHT:** electronics: 2.3 kg (6.5 lb)

detectors 14.5 kg (32 lb) each