

Ludlum Measurements, Inc. 501 Oak Street P.O. Box 810 Sweetwater, TX 79556 Tel: 325-235-5494 Fax: 325-235-4672 www.ludlums.com

MODEL 375 NETWORK SETTINGS REQUEST FORM

Please fill out the following information so the network settings can be configured before the instrument leaves the factory. This form must be filled out for each Model 375 Area Monitor. Contact your IT department for the appropriate values.

Contact Information		
Company Name	Sales Order #	
Contact E-Mail		
IT Contact E-Mail		

Please select which software the Model 375 will be configured for:

○ 1370-055 Ethernet Software - Monitor broadcasts UDP message at fixed intervals.

C 1370-077 Web Page and Service Software - Monitor connects to central server using TCP connection and sends current readings at fixed intervals.

IP Address Configuration					
	◯ Static	IP Address			
		Subnet Mask			
		Gateway IP Address			
		DNS IP Address			
service listens on for incomin	g connections f		rvisor Prin	hary and Secondary IP a	ort number is the port that Supervisor ddresses are the IP address that the e.
TCP Port Number				Camera Enabled	
Supervisor Primary IP Address				Camera IP Address	
Supervisor Secondary IP Address				Camera Password	
This section applies to a Mod to 59999.	el 375 that will l	be configured for use the 1370-05 .	5 Etherne	t Software. The UDP Po	rt number must be in the range of 50000
Unit ID				Camera Enabled	
UDP Port Number (50000-59999)				Camera IP Address	
This section to be filled out by	y Ludlum Measu	urements, Inc.			
Model/Serial Number			24 Hour Burn- in Test		
Instrument Firmware			Functional Check		
Ethernet Firmware					
MAC Address					
Performed By:		Date:			
Reviewed By:	Ву:		Date:		