

# Model 30-7 Series Lightweight Digital Neutron Detector



Ludlum Measurements, Inc.

## Features

- Small & Light 19.5 cm (7.7 in.) REM Ball
- Moderated Neutron Detector
- Digital Display with Adjustable Viewing Angle
- Range: 0–99.9 mSv/h (0–9.99 rem/hr)
- Low-Weight Unit Provides Same Readings as Standard REM-ball from Bare AmBe and Lower Energies
- Includes Adjustable Shoulder Strap



upper left: with included shoulder strap  
bottom: detail of digital display unit

## Specifications

**Model 30-7** Part Number: 48-4192

**Model 30-7B** Part Number: 48-4309

**INDICATED USE:** Neutron dose rate

**DETECTOR:**  $^3\text{He}$  proportional detector, 1.6 x 2.5 cm (0.6 x 1.0 in.) (D x L), surrounded by a 19.5 cm (7.7 in.) diameter polyethylene sphere with internal borated layer

**MEASUREMENT RANGE:** 0 to 99.9 mSv/h (0 to 9.99 rem/hr)

**SENSITIVITY (bare AmBe neutrons):**

*Model 30-7:* Typically 10 cpm per  $\mu\text{Sv/h}$  (100 cpm per mrem/hr)

*Model 30-7B:* Typically 4.5 cpm per  $\mu\text{Sv/h}$  (45 cpm per mrem/hr)

**ENERGY RESPONSE:** Provides appropriate inverse RPG curve for neutrons from thermal through 7 MeV, provides response up to 12 MeV (see graphs on back). Model 30-7 tends to overrespond in the 5 keV range.

**LINEARITY:** Reading within 10% of actual value

**GAMMA REJECTION:** < 10 cpm through 0.1 Sv/h (10 R/hr) ( $^{137}\text{Cs}$  gamma)

**LCD DISPLAY:** 3 digit LCD with large 13.4 mm (0.53 in.) digits, (k)cps, (k)cpm, ( $\mu$ )(m)Sv/(h), ( $\mu$ )(m)rem/(h), low-battery indicator, MAX, ALARM, MUTE

**DISPLAY RANGE:** 0.0 cps to 99.9 kcps; 0.00 cpm to 999 kcpm; 0.00 rem/hr to 999 rem/hr; 0.00  $\mu\text{Sv/h}$  to 999 Sv/h. Display range can be set to limit display to calibrated range

**BACKLIGHT:** Built-in ambient light sensor automatically activates low-power LED backlight, unless internal dipswitch is set to continuous (will reduce battery life). Alarm light intensity varies based on ambient light levels.

**USER CONTROLS:**

- ON/OFF/ACK - Press to turn ON; Tap to acknowledge alarms and silence alarm tone; Press to reset Sigma Audio alarm; Turn "click" audio On/Off; Turn Sigma Audio beep On/Off; Hold for OFF
- MODE - Alternates between NORMAL (count rate), MAX (captures peak rate), and COUNT (user-selectable preset count time from 0 to 10 minutes). Number of modes can be reduced in setup.
- UNITS - Changes the units between count rate (cpm, cps), or dose/exposure ( $\mu\text{Sv/h}$ , rem/hr)

**RESPONSE TIME:** User-selectable from 1 to 60 seconds, or Auto-Response Rate FAST or SLOW

**ALARMS:** Count rate, exposure/dose, and scaler alarm setpoints adjustable over the display range

**OVERLOAD:** High count rate saturation protection prevents false display of lower count rates

**ZERO PROTECTION:** After a user-settable time interval (default 60 seconds) of no pulses from detector, the instrument will flash zero reading and the alarm audio will be triggered

**DEAD TIME CORRECTION:** Employs first and second order corrections for extended performance

**OPERATING VOLTAGE:** Approximately 1200 Vdc

**THRESHOLD:** -2 mV

**AUDIO:** Greater than 75 dB at 0.6 m (2 ft), approximately 4 kHz

**POWER:** Two alkaline or two rechargeable "AAA" batteries

**BATTERY LIFE:** Approximately 100 hours of operation, 24-hour low battery warning

**CONSTRUCTION:** High-impact plastic with water-resistant rubber seals and separate battery compartment

**WORKING ENVIRONMENT:** Splashproof shields for outdoor use

**TEMPERATURE RANGE:** -20 to 50 °C (-5 to 122 °F), may be certified for operation from -40 to 65 °C (-40 to 150 °F)

**ENVIRONMENTAL RATING:** NEMA rating of 3x or IP rating of 52 with audio hole seal option (hole seal option will reduce maximum volume by approximately 10 dB)

**SIZE:** Display Unit: 8.5 x 8.0 x 4.8 cm (3.4 x 3.1 x 1.9 in.) (H x W x L); Detector: 19.5 cm (7.7 in.) REM ball with  $^3\text{He}$  detector (1.6 x 2.5 cm)

**WEIGHT:** Display Unit: 174 g (0.38 lb); REM Ball Component: 4.6 kg (10.2 lb)

**OPTION:** Transport and Storage Case (P/N 2311487)

Ludlum Measurements, Inc. P.O. Box 810, Sweetwater, Texas 79556

Web: <http://www.ludlums.com> Tel: 800-622-0828 / 325-235-5494 / Fax: 325-235-4672 / Email: [sales@ludlums.com](mailto:sales@ludlums.com)

Note: specifications subject to change without notification. We are not responsible for errors or omissions.

Feb 2020

Comparison of the Energy Response Curves for the Model 30-7B and Thermo's 4 atm NRD REM Meter

