

Model 9DP-1 Pressurized Ion Chamber

Part Number: 48-3899

Features

- Range: 2 $\mu\text{Sv/h}$ to 500 mSv/h (200 $\mu\text{R/hr}$ to 50 R/hr)
- Special Design for Measuring Pulsed Fields
- Low Pressure Chamber is Non-Hazmat
- Shows Exposure Rate & Either Integrated Exposure or Peak Exposure Rate
- Pulsed Mode for Measuring Pulsed Radiation
- Sunlight Readable Color Display
- Auto-Zeroing & -Ranging
- Rechargeable Batteries
- Audio & Visual Alarms
- Data Logging
- USB Connectivity
- Free Firmware Updates Through Website

Introduction

The Model 9DP-1 is a digital, hand-held pressurized ion chamber that provides highly sensitive exposure measurements of gamma and x-ray radiation at energies above 25 keV and beta radiation at energies above 1 MeV. This meter is specially designed for radiography work where pulsed fields are being measured. It correctly integrates 50 ns pulses (and wider) that other systems typically miss or measure inaccurately. Another feature of this instrument is that the detector chamber is only pressurized to 2.5 atm (22 psig), thus avoiding all (USA) HAZMAT concerns for shipping and handling. However, this reduced pressure also reduces sensitivity, so the minimum "good" measurement point is 2 $\mu\text{Sv/h}$ (200 $\mu\text{R/hr}$).

Measurements and instrument status are displayed on a large 232K-color, backlit LCD screen. The screen displays the current exposure rate as well as simultaneously displaying either the integrated exposure rate or the peak exposure rate in Sv, R, Gy, or rem units. An additional mode, Pulsed Mode, locks the instrument in the highest measurement range in order to improve pulsed radiation response while sacrificing low radiation reading resolution.

The instrument is operated using the four push-buttons below the screen (ON/OFF, FUNCTION, AUDIO, ACK/RESET). In addition to the visual display, click audio proportional to the current exposure rate audibly indicates the exposure rate level. Two alarm levels can be set to alert the user whenever the pre-programmed level has been exceeded. Alarms are indicated on the display and by an audio tone. The instrument can also be configured for data logging. Logged data can either be stored in CSV format and written to a standard USB drive inserted in the instrument's USB port, or written directly to a Microsoft Excel spreadsheet by connecting the instrument to a computer running Ludlum's Model 9DP Logging Spreadsheet Software (see options below).

The Model 9DP parameter settings can be edited by connecting the instrument to a basic USB keyboard. Instrument setup and calibration can also be configured using the Ludlum Dimension Interface Kit, which includes the Dimension Configuration Manager Software and the required USB cable (see options below).

Options

- Dimension Interface Kit (PN: 4293-763)
- Logging Spreadsheet Software Package (PN: 4293-998)
- Headphone Jack (PN: 4293-891)
- Alkaline Battery Pack (non-rechargeable) (PN: 4543-028)
- Check Source, 10 μCi ^{137}Cs (PN: 01-5231)
- Transport & Storage Case (PN: 2311063)
- Shoulder Strap (PN: 4536-632)
- USB Keyboard (PN: 2312289)



Control Buttons



Headphone Jack
Option



Portable USB Drive
(included)



Alkaline
Battery Pack
Option



Transport & Storage Case
Option

Ludlum Measurements, Inc. P.O. Box 810, Sweetwater, Texas 79556

Web: ludlums.com Tel: 800-622-0828 / 325-235-5494 Fax: 325-235-4672 Email: sales@ludlums.com

Note: specifications subject to change without notification. We are not responsible for errors or omissions.

Jul 2023

Specifications

RADIATION DETECTED: gamma & X-rays above 25 keV, beta above 1 MeV, correctly integrates pulsed fields with 50 ns pulse widths

ENERGY RESPONSE: $\pm 25\%$ from 60 keV to 1.25 MeV (see graph below)

DISPLAY RANGES: (auto-ranging)

- Sv/h units*: 2–50 μ Sv/h, 2–500 μ Sv/h, 0–5 mSv/h, 0–50 mSv/h, 0 – 500 mSv/h
- R/hr units: 0.2–5 mR/h, 0.2–50 mR/h, 0–500 mR/h, 0–5 R/h, 0–50 R/h
- Gy/h units: 2–50 μ Gy/h, 2–500 μ Gy/h, 0–5 mGy/h, 0–50 mGy/h, 0–500 mGy/h
- rem/h units: 0.2–5 mrem/h, 0.2–50 mrem/h, 0–500 mrem/h, 0–5 rem/h, 0–50 rem/h

* Users wanting to take measurements in Sv/h units should see the Ludlum Model 9DP-1* which is specifically designed to measure ambient equivalent dose.

MEASUREMENT READOUTS: simultaneous display of rate and either the integrated value, highest (peak) rate, or pulsed mode status

DRIFT: less than 0.3 μ Sv/h (30 μ R/hr, 0.3 μ Gy/h, 30 μ rem/h)

CHAMBER VOLUME: 220 cc (13.4 in³) volume pressurized to 2.5 atm (22 psig)

CHAMBER DENSITY: chamber wall density is 601.7 mg/cm², can wall density is 332.5 mg/cm². Total density of chamber + can is 934.2 mg/cm²

ACCURACY: $\pm 10\%$

RESPONSE TIME: ranges from 7 seconds in lowest range to under 2 seconds in highest range when measuring from 10% to 90% of final value

DISPLAY: LCD with 8.9 cm (3.5 in.) diagonal, 240 H x 320 W pixels, TFT active matrix, 232K colors, 220 cd/m², automatic sensor-controlled backlighting

USER CONTROLS: 4 push buttons: ON/OFF; FUNCTION (for peak rate, integrate, or pulsed modes); AUDIO (on/off, volume); and ACK/RESET (for alarm acknowledgement, meter reset, and clearing integrated exposure or peak rate)

AUTOMATIC FUNCTIONS: auto-ranging, auto-zeroing, auto LCD backlighting

ALARMS: Two levels of radiation alarms available, each is user programmable throughout entire readout range.

DATA LOGGING: Data is stored to detachable USB drive in CSV format for easy retrieval by PC spreadsheet/database programs. Data points include date and time, rate, integrated reading, and instrument status. Logging time intervals are set by PC interface program or USB keyboard.

AUDIO OUTPUTS: built-in unimorph speaker, > 60 dB at 0.6 m (2 ft), optional audio jack available for connection to external headset

USB INTERFACE: single USB 2.0 port. May be connected directly to a USB keyboard (with no additional USB ports, and no integrated mouse or trackpad or audio controls) to facilitate password-protected parameter changes. Accepts USB memory storage device for storing logged data. Optional Dimension Interface Kit (PN 4293-763) facilitates connection to a PC for parameter editing and calibration.

WARM UP TIME: < 1 minute when the instrument is in temperature equilibrium with the surrounding environment

TEMPERATURE RANGE: -20 to 40 °C (-4 to 104 °F)

HUMIDITY: 0–95%, non-condensing

GEOTROPISM: less than 1%

POWER: eight rechargeable AA NiMH batteries, supplied with wall charger for direct connection to instrument


BATTERY LIFE: approximately 12 to 30 hours between charges depending on backlighting and USB usage

CONSTRUCTION: durable molded plastic with internal metal support


SIZE (H x W x L): 21.9 x 11.6 x 24.5 cm (8.6 x 4.6 x 9.6 in.)

WEIGHT: 1.5 kg (3.3 lb), including batteries

**Model 9DP-1 Exposure Energy Response
Relative to Cs-137**



Angular Dependence



Ludlum Measurements, Inc. P.O. Box 810, Sweetwater, Texas 79556

Web: ludlums.com **Tel:** 800-622-0828 / 325-235-5494 **Fax:** 325-235-4672 **Email:** sales@ludlums.com

Note: specifications subject to change without notification. We are not responsible for errors or omissions.